

⑤ PIN

(DI) 4 CADMIUM PLATE PER QQ-P-416 TYPE II CLASS 2.
3 TOP OF -5 PIN TO BE FLUSH WITH TOP OF
-3 BARREL WITHIN .002

1. BREAK EDGES .015 R OR .015x45° CHAMFER EXCEPT AS NOTED.

NOTES:

SHOP COPY

T101506

D

[illegible]

LIST OF MATERIAL OR PARTS LIST

EWA 206 CA-4.3

W.O. 2301


[illegible]

INTERCHANGEABLE
AND SUPERSEDED
BY STANDARD 170-001

FIED AND APPROVED
ANDARDS AND MATE-
LISTED IN REPORT

SHOP COPY

WELD - TYP - BOTH SIDES



T!01506 SLEEVE

REVISIONS		
NO.	DESCRIPTION	DATE APPROVED
A	CHG. FROM TEST TO PROD. DWG. REF. TEST E.O. 206 CA 370 (V)	12-14-66 L. Wood
B	ADDED PROPRIETARY DECAL AND N/A REQUIREMENTS	2-20-70 J. YOUNG
C	INC. (1) E.O. 206GA-1534, ADDED N/A REQ. MTS FOR 206B, 206B-1, 206B-1 (AUST.), COH-58A, 24-735	SHIFFLETT
D	SEE E.O. (1) 206C/A 224 AND ADDED SUPERSEDED + SOURCE DECALS	7-23-80 RAMIREZ

TOOL USAGE BLOCK

COLUMN	V2	V3	V4	V5	V6	V7	V8
PARA	REMARKS	TOOL NO.	OPER	P/N & NAME	OPER	P/N & NAME	ON ASSY NO.
1	206 SERIES	T!01506	INSTALL REMOVE	206-040-043 SHAFT	INTO FROM	206-040-035 BEARING	206-040-006

